

Technical Data Sheet

EPDM 70 Rubber Sheet

Features: Shuk EPDM 70 Rubber is a black premium grade 70 Duro EPDM Rubber sheet, which has high temperature resistance and chemical resistance to acids and alkalis. It is completely UV stabilised making it highly resistant to ozone effects and extreme weather conditions and is ideal for long term outdoor applications.

Shuk EPDM 70 Rubber has excellent physical properties including mechanical strength and is resistant to hot water and steam. It is suitable for prolonged exposure to aquatic environments and will not deteriorate when submerged in fresh or seawater making it suitable for marine applications.

Applications: Shuk EPDM 70 Rubber Sheet has been designed primarily for use as a flexible strip, pad, lining or gasket and is mainly used for Sealing, Insulating, Isolating and Protecting steel or other surfaces. Its properties make it suitable for a number of applications including:

- Flange gaskets on pipes and tanks
- Lining of pipes and tanks
- Transfer and joining sleeves
- Weatherproof flashing
- Insulating strip
- Isolation barriers
- Heat resistance skirting rubber and belt scrapers
- Dust covers exposed to extreme weathering and operating temperatures
- Variety of underwater applications

Dimensions:

GMEPDM1.6	1.6mm Thick
GMEPDM4.5	4.5mm Thick
GMEPDM6.4	6.4mm Thick
GMEPDM9.5	9.5mm Thick

Technical Information:

Polymer	EPDM	
Colour	Black	
Specific Gravity	1.15	ASTM D297
Hardness	70° ± 5° Shore A	ASTM D2240
Abrasion	275 (max) @ 1ON	ASTM D5963
Tensile Strength	11 MPa (min)	ASTM D412
Elongation @ Break	350% (min)	ASTM D412
Tear Strength	45 N/mm (min)	ASTM D624
Temperature Range	-30°C to +120°C	